

ORINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date: Specification Section:

Originator: Articles/Subarticles:

Telephone:

email:

Will the proposed revision involve Design Standard Index changes? Yes No

Roadway Design staff contacted (name):

Structures Design staff contacted (name):

Will the proposed revision involve PPM changes? Yes No

Roadway Design staff contacted (name):

Will the proposed revision involve CPAM changes? Yes No

Construction staff contacted (name):

Will the proposed revision involve Pay Item changes? Yes No

Estimates staff contacted (name):

Will the proposed revision involve SDG changes? Yes No

Structures staff contacted (name):

Will the proposed revision involve APL changes? Yes No

Product Evaluation staff contacted (name):

Will the proposed revision involve Material Manual changes? Yes No

State Materials Office staff contacted (name):

Will this revision necessitate any of the following:

Design Bulletin Construction Bulletin Estimates Bulletin Materials Bulletin

Are all references to external publications current? Yes No

If not, what references need to be updated? (Please include changes in the redline document.)

Why does the existing language need to be changed?

Summary of the changes:

Are these changes applicable to all Department jobs? Yes No

If not, what are the restrictions?

Contact the State Specifications Office for assistance in completing this form.

Daniel Scheer 850-414-4130 daniel.scheer@dot.state.fl.us

Debbie Toole 850-414-4114 deborah.toole@dot.state.fl.us

Frances Thomas 850-414-4101 frances.thomas@dot.state.fl.us

Olivia Townsend 850-414-4303 olivia.townsend@dot.state.fl.us



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

JIM BOXOLD
SECRETARY

MEMORANDUM

DATE: October 1, 2015

TO: Specification Review Distribution List

FROM: Daniel Scheer, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: **5140000 Plastic Filter Fabric (Geotextile)**.

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Missy Hollis of the Estimating System Support Office to modify the language to clarify the basis of payment.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at <http://www2.dot.state.fl.us/ProgramManagement/Development/IndustryReview.aspx> . Comments received after **October 29, 2015**, may not be considered. Your input is encouraged.

DS/dt
Attachment

PLASTIC FILTER FABRIC (GEOTEXTILE)
(REV 9-21-15)

SECTION 514 is deleted and the following substituted:

SECTION 514
PLASTIC FILTER FABRIC (GEOTEXTILE)

514-1 Description.

Install a plastic filter fabric.

514-2 Material.

Meet the plastic filter fabric requirements as specified in Section 985.

514-3 Construction Methods.

514-3.1 General: Place the fabric in the manner and locations as shown on the construction drawings, in accordance with the manufacturer's directions, and as specified in these Specifications. Place the fabric on areas with a uniform slope that are reasonably smooth, free from mounds and windrows, and free of any debris or projections which might damage the fabric.

Loosely lay the material. Do not stretch the material. Replace or repair any fabric damaged or displaced before or during placement of overlying layers to the satisfaction of the Engineer and at no expense to the Department.

When overlapping is necessary, the Contractor may sew the seams to reduce overlaps as specified in 985-3.

Schedule work so that covering the fabric with the specified material does not exceed the manufacturer's recommendations for exposure to ultraviolet light or five days, whichever is less. If the Engineer determines the exposure time was exceeded, the Contractor shall replace the fabric at no expense to the Department.

514-3.2 Subsurface Drainage: When indicated in the Plans, place the fabric with the long dimension parallel to the trench. Place the fabric to provide a minimum 12 inch overlap for each joint. Do not drop the filter material from heights greater than 3 feet.

514-3.3 Stabilization and Reinforcement: Overlap adjacent strips of fabric a minimum of 24 inches.

514-3.4 Riprap Filter: Overlap adjacent strips of fabric a minimum of 24 inches, and anchor them with securing pins (as recommended by the manufacturer) inserted through both strips of fabric along a line through the midpoint of the overlap and to the extent necessary to prevent displacement of the fabric.

Place the fabric so that the upstream (upper) strip of fabric overlaps the downstream (lower) strip.

Stagger vertical laps a minimum of 5 feet. Use full rolls of fabric whenever possible in order to reduce the number of vertical laps.

Do not drop bedding stone or riprap from heights greater than 3 feet onto the fabric.

514-4 Method of Measurement.

~~When separate payment is indicated in the Plans, the quantity to be paid for included will be the area, in square yards, of plastic filter fabric placed excluding all laps, completed and accepted.~~

~~When no separate payment for furnishing and placing the plastic filter fabric is contained in the proposal, the Contractor shall include the cost of all work in the Contract price for the item or items to which it is incidental.~~

514-5.4 Basis of Payment.

~~Price and~~ **No separate** payment will be **full compensation made** for **all the** work specified in this Section, **including. The cost of** furnishing, placing, and sewing or overlapping the fabric **will be included in the Contract price for the items to which it is incidental.**

~~Payment will be made under:~~

~~Item No. 514-71 Plastic Filter Fabric per square yard.~~