

ORINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date: Specification Section:

Originator: Articles/Subarticles:

Telephone:

email:

Will the proposed revision involve Design Standard Index changes? Yes No

Roadway Design staff contacted (name):

Structures Design staff contacted (name):

Will the proposed revision involve PPM changes? Yes No

Roadway Design staff contacted (name):

Will the proposed revision involve CPAM changes? Yes No

Construction staff contacted (name):

Will the proposed revision involve Pay Item changes? Yes No

Estimates staff contacted (name):

Will the proposed revision involve SDG changes? Yes No

Structures staff contacted (name):

Will the proposed revision involve APL changes? Yes No

Product Evaluation staff contacted (name):

Will the proposed revision involve Material Manual changes? Yes No

State Materials Office staff contacted (name):

Will this revision necessitate any of the following:

Design Bulletin Construction Bulletin Estimates Bulletin Materials Bulletin

Are all references to external publications current? Yes No

If not, what references need to be updated? (Please include changes in the redline document.)

Why does the existing language need to be changed?

Summary of the changes:

Are these changes applicable to all Department jobs? Yes No

If not, what are the restrictions?

Contact the State Specifications Office for assistance in completing this form.

Daniel Scheer 850-414-4130 daniel.scheer@dot.state.fl.us Debbie Toole 850-414-4114 deborah.toole@dot.state.fl.us
Frances Thomas 850-414-4101 frances.thomas@dot.state.fl.us Olivia Townsend 850-414-4303 olivia.townsend@dot.state.fl.us



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

JIM BOXOLD
SECRETARY

M E M O R A N D U M

DATE: November 12, 2015

TO: Specification Review Distribution List

FROM: Daniel Scheer, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: **7100401 Painted Pavement Markings.**

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Chester Henson of the State Roadway Design Office to modify the language for current Department practice.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at

<http://www2.dot.state.fl.us/ProgramManagement/Development/IndustryReview.aspx> .

Comments received after **December 10, 2015**, may not be considered. Your input is encouraged.

DS/dt
Attachment

PAINTED PAVEMENT MARKINGS.
(REV 11-3-15)

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

710-4.1.1 Painted Pavement Markings (Final Surface): ~~When permanent pavement markings (i.e., thermoplastic or permanent tape), are placed on~~ On concrete surfaces or newly constructed asphalt without rumble striping, the painted pavement markings (final surface) will include one application of standard paint and one application of Class B retroreflective pavement markers applied to the final surface. ~~Wait at least 14 days after the application of painted pavement markings (final surface) to apply the thermoplastic. No minimum wait period is required for permanent tape.~~

~~When permanent pavement markings rumble striping is~~ are placed on newly constructed asphalt with rumble striping, apply two applications of standard paint, ~~and one application of Class B~~ **BD** retroreflective pavement markers, ~~if applicable, and one application of Class B~~ **DB** retroreflective pavement markers. ~~Additionally, F~~ **For** center line rumble striping installations, install Class D retroreflective pavement markers, ~~Remove them~~ **Class D markers** prior to grinding, and install Class B retroreflective pavement markers **in an unground area on** ~~the non-ground surface~~ after grinding. ~~The~~ **A** second application of standard paint must be applied within 24 hours of each day's grinding operation. ~~Wait at least 14 days after the first application of painted pavement markings (final surface) to apply the thermoplastic.~~

~~When no permanent pavement markings are placed, the painted pavement markings (final surface) will include two applications of standard paint and one application of Class B retroreflective pavement markers applied to the final surface. Wait at least 14 days after the first application of painted pavement markings (final surface) to apply the second application of paint.~~

Apply all retroreflective pavement markers in accordance with Design Standards, Index No. 17352, prior to opening the road to traffic.

~~The final application of pavement markings must be applied prior to final acceptance of the project.~~

Apply all temporary retroreflective pavement markers meeting the requirements of Section 102.

Apply all permanent retroreflective pavement markers meeting the requirements of Section 706.