

EXPECTED IMPLEMENTATION JULY 2016

994 RETROREFLECTIVE AND NONREFLECTIVE SHEETING AND SIGN PANEL FABRICATION.

(REV 11-4-15) (FA 1-18-16) (7-16)

SUBARTICLE 994-2.3.3 is deleted and the following substituted:

994-2.3.3 Clear Overlay Films: Clear overlay film must be compatible with the sign sheeting system and not delaminate or discolor for the in-service life of the system. Submit spectrophotometer analysis indicating the luminous transmittance across the wavelength range from 325 nm to 700 nm in accordance with ASTM D1003 Procedure B. Film shall filter less than 1.0% luminous transmittance for 325 nm to 350 nm.

SUBARTICLE 994-2.3.3 is deleted and the following substituted:

994-3.4 Fabrication of Sign Blanks: Fabricate all metal parts to ensure a proper fit of all sign components. Complete all fabrication, with the exception of cutting and punching of holes, prior to metal de-greasing and applying the retroreflective sheeting. Cut metal panels to size and shape and keep free of buckles, warp, dents, burrs, and defects resulting from fabrication. Use aluminum sheets with increments of 4 feet in width; except, for sign widths that are not multiples of 4 feet. A maximum of two panels may be cut to less than 4 feet, and no panel may be cut to less than one foot. Mount aluminum sheets vertically and provide backing strips at vertical joints to keep the abutting sheets in proper alignment.

Ship all multi-panel signs to the project intact, completely assembled and ready to be installed. Fabricate signs taller than 10 feet as two separate signs with a horizontal splice, ready to be spliced and installed.