

SECTION 954 TIMBER FENCE POSTS AND BRACES

954-1 Types of Timber, and Treating Requirements.

Timber fence posts and braces shall be of southern yellow pine and shall be treated in accordance with Section 955.

Prior to the treatment, all knots on the posts shall be trimmed close to the body of the post.

954-2 Requirements for Cutting.

Round or square posts will be permitted but all posts on a single project shall be the same. The posts shall be cut from sound and solid trees and shall contain no unsound knots. The butt shall be cut at a sufficient distance above the ground swell of the tree that there will be no abrupt change in cross-section of the post.

The butts shall be sawn square. The post tops shall be sawn neatly and at right angles to the vertical axis of the post.

954-3 Knots, etc.

Sound knots will be permitted provided the diameter of the knot does not exceed 1/3 of the diameter of the piece at the point where it occurs.

Peck (in cypress posts) shall be limited as provided for knots; the area of permissible peck not exceeding the area occupied by permissible knots, and a combination of peck and knots not exceeding the aggregate of knots allowed.

The posts shall be free from decayed wood, rot, and red heart, and of ring shake or season checks which penetrate at any point more than 1/4 the diameter of the piece, or are greater than 1/4 inch [6 mm] wide.

954-4 Peeling.

All posts shall be peeled for their full length, and all inner and outer bark removed, except that isolated strips of inner bark which do not exceed 1/2 inch [13 mm] in width or 3 inches [75 mm] in length will be permitted.

954-5 Straightness.

The straightness of the post shall be such that for any 8 foot [2.5 m] post (or for any 8 feet [2.5 m] of length, for longer posts) a straight line from the center of the tip to the center of the butt (or from center of the cross sections at the extremes of the 8 foot [2.5 m] lengths) shall not fall outside the center of the mid-section of the 8 foot [2.5 m] length by more than 2 inches [50 mm].

954-6 Dimensions.

954-6.1 Minimum Lengths Allowable:

Line posts - 8 feet [2.5 m].

Corner and pull posts - 8 feet, 6 inches [2.6 m].

Braces - As required by plans.

(A tolerance of -1 inch + 2 inches [25 or +50 mm] will be allowed in the lengths shown for the posts.)

954-6.2 Minimum Allowable Cross Section:

Round line posts - 4 inch [100 mm] diameter.

Round braces, corner and pull posts - 5 inch [125 mm] diameter.

Square line posts - 4 by 4 inches [89 by 89 mm].

Square braces, corner and pull posts - 5 by 5 inches [114 by 114 mm].

The minimum diameters specified for round posts are applicable before preservative treatment. When the treated post is inspected at the job site a tolerance of 3/8 inch [10 mm] under such diameters will be allowed, to compensate for shrinkage resulting from treatment and storage.