

EXPECTED IMPLEMENTATION JANUARY 2007

649 STEEL STRAIN POLES, STEEL MAST ARM AND MONOTUBE ASSEMBLIES. (REV 6-11-06) (FA 7-24-06) (1-07)

SECTION 649 (Pages 701-705) is deleted and the following substituted:

SECTION 649 STEEL STRAIN POLES, STEEL MAST ARM AND MONOTUBE ASSEMBLIES

649-1 Description.

The work in this Section consists of furnishing and installing steel strain poles, steel mast arm(s) and monotube assemblies in accordance with the details shown in the Contract Documents.

649-2 Materials.

Use Steel Strain Poles, Steel Mast Arm and Monotube Assemblies listed on the Department's Qualified Products List (QPL) for all standard configurations shown in the Design Standards.

Provide shop drawings and signed and sealed calculations, as needed, in accordance with Section 5 for configurations shown in the plans and denoted as special.

Use coating products meeting the requirements of Section 975 listed on the QPL.

Use grouts meeting the requirements of Section 934 listed on the QPL.

Use water meeting the requirements of Section 923.

Use membrane curing compounds meeting the requirements of Section 925.

649-2.1 Certification: Provide the Engineer with certified test reports from the manufacturer confirming that all materials conform to the requirements of this Section, Section 6, and the Design Standards. Provide the Engineer a copy of the Certificate of Compliance at least 10 days prior to installation. Acceptance of the furnished material will be based on the Certificate of Compliance and visual inspection by the Engineer.

649-3 Fabrication.

Fabricate steel strain poles, steel mast arm and monotube assemblies and miscellaneous hardware in accordance with the Contract Documents. Cut all materials to the final dimensions and complete all welding prior to galvanizing. Obtain all components for individual steel strain poles, steel mast arm and monotube assemblies from the same fabricator. Obtain the luminaire and bracket from other sources, when necessary.

Affix an aluminum identification tag which will be visible from the handhold or located inside the terminal box containing the information described in the Design Standards.

Before shipping, assemble steel mast arm and monotube assemblies including luminaire and bracket, to assure proper fit. The steel mast arm and monotube assemblies may be separated for shipment.

Ensure all components are protected from damage during shipping and handling by wrapping or other effective methods. Replace any component, which the Engineer determines is damaged beyond repair, at no additional cost to the Department. If components are wrapped for shipment, remove wrappings no later than five days after receipt of components or immediately if the wrappings become saturated. Post these instructions in brightly colored wording on the

EXPECTED IMPLEMENTATION JANUARY 2007

wrapper. Failure to comply with these instructions may lead to damage of the coating system and will be cause for the rejection of the component.

649-4 Coatings.

649-4.1 Galvanizing: Galvanize all components in accordance with ASTM A 123. Use galvanizing methods which provide surfaces suitable for painting.

649-4.2 Surface Preparation: Prepare all galvanized surfaces to be painted in accordance with ASTM D 6386 and the manufacturer of the coating system's specifications. Provide a clean and suitable galvanized surface that maximizes coating system adhesion.

Measure the thickness of the zinc coating after completion of surface preparation using a magnetic thickness gage in accordance with ASTM A 123. Ensure sufficient galvanizing remains on the substrate to meet the requirements of ASTM A 123 and the Contract Documents. Correct any deficient areas to the satisfaction of the Engineer at no additional cost to the Department.

649-4.3 Painting: When required by the Contract Documents, paint steel strain poles, steel mast arms and monotube assemblies, in accordance with Sections 560, 562 and these Specifications. Meet the color requirement as specified in the Contract Documents. Provide the Engineer with two sample coupons, 2 x 4 inches, of the color and paint system proposed.

649-4.4 Application of the Paint System: Apply the paint system according to the manufacturer's recommendations. Test coating thickness and cure after completion of each coat to ensure the coating meets the requirements of the manufacturer's recommendations using SSPC-PA2. Correct any deficient areas to the satisfaction of the Engineer at no additional cost to the Department.

Correct any deficient or damaged areas to the satisfaction of the Engineer at no additional cost to the Department.

649-5 Installation.

Install foundations for steel strain poles, steel mast arm and monotube assemblies in accordance with Section 455. Do not install the steel mast arm pole, strain poles or monotube pole until the foundation has cured for a minimum of seven days. Before erecting the pole clean the top of the foundation of any laitance, oils, grease or any other deleterious materials. Erect strain poles in an orientation which considering the rake and the application, cable forces will produce a plumb pole. Erect monotubes plumb at the time of installation. Plumb the pole supporting mast arms after the mast arms, traffic signals or sign panels have been placed.

If the traffic signals and/or sign panels are not in place within two working days after the mast arm is erected, furnish and install a 3 by 2 foot blank sign panel on the bottom of each mast arm within 6 feet of the mast arm tip and plumb the pole. Re-plumb the pole supporting mast arms after installation of traffic signals and sign panels.

Install bolt, nut and washer assemblies, except nuts on anchor rods, in accordance with Section 460. Install nuts on anchor rods in accordance with the following: use anchor bolt assemblies that are free of rust and corrosion, and lubricate these assemblies prior to installation so that the nut moves freely by hand through the full length of the thread. Bring the lower top anchor nuts on the anchor rods to a "snug tight" condition defined as: the tightness that is attained with a few impacts of an impact wrench or the full effort of an ironworker using an ordinary spud wrench such that more than 75% of the faying surfaces are in firm contact. Before snugging the lower top anchor nuts, all bottom leveling nuts shall be leveled. After snugging the lower top anchor nuts, all bottom leveling nuts shall be tightened to the base plate by full effort of an ironworker using an ordinary spud wrench. Use a beveled washer if outer face of the base

EXPECTED IMPLEMENTATION JANUARY 2007

plate is sloped more than 1:40 or if necessary to attain “snug tight” condition. After attaining “snug tight” condition, additionally tighten the lower top anchor nuts on the anchor rods in accordance with Table A. Nut rotation is relative to anchor rod, tolerance is plus 20 degrees. Install the upper top anchor nuts on the anchor rods on top of the lower top anchor nuts using the tightness that is attained with a few impacts of an impact wrench or the full effort of an ironworker using an ordinary spud wrench. During the tightening of the upper top anchor nuts, the lower top anchor nuts shall be restrained from movement by using an ordinary spud wrench.

Anchor Rod Diameter (in.)	Nut Rotation from snug Tight Condition
$\leq 1 \frac{1}{2}$	1/3 turn
$> 1 \frac{1}{2}$	1/6 turn

649-6 Grouting.

649-6.1 Preparation: Flush the top of the foundation with clean water to remove any dirt and debris. Immediately before grouting, saturate the concrete surfaces by ponding or by placement of saturated rags for a minimum period of two hours. Remove all freestanding water before beginning the grouting operation.

649-6.2 Forming: Use watertight non-absorbent forms with a form release agent applied to all interior surfaces. Maintain a 1 inch clearance between the forms and the base plate. Extend the form a minimum of 1 inch above the bottom of the base plate. Attach a head box with a 45 degree slope on the form for grout placement.

649-6.3 Mixing: Use only fresh unopened full bags of grout. Mix the grout in a clean, power driven mortar mixer or with a heavy duty drill (850 RPM maximum) using a commercial mixing paddle. Mix the grout in accordance with the manufacturer’s instructions. Test the fluidity of the grout using the ASTM C 939 Flow Cone Method. Use grouts that meet the efflux time of 20 to 30 seconds. Do not remix grouts that have begun to set.

649-6.4 Placing and Curing: Pour the grout from only one side of the base plate through the head box until the grout has filled the entire form and extends a minimum of 1/4 inch above the bottom of the base plate. Do not allow the grout to overtop the base plate. Do not vibrate grout. Clean excess grout off the base plate after the grout has reached initial set (two to four hours). Cure the grout for a minimum of six hours by covering the entire grout surface with clean saturated rags. Remove the forms after verifying the grout is self supporting by penetration with a pointed masons trowel or other sufficient tool. Cure all exposed grout with a membrane curing compound.

649-7 Method of Measurement.

649-7.1 General: Measurement for payment will be in accordance with the following work tasks.

649-7.2 Furnish and Install: The Contract unit price each for steel strain poles, steel mast arm and monotube assemblies, furnished and installed, will include all materials specified in the Contract Documents, including the foundation, cover plates, caps, clamps, blank sign panel, luminaire bracket, all labor, equipment, miscellaneous materials and hardware necessary for a complete and acceptable installation.

649-7.3 Furnish: The Contract unit price each for steel strain poles, steel mast arm and monotube assemblies, furnished, will include all materials, all shipping and handling costs involved in delivery as specified in the Contract Documents.

EXPECTED IMPLEMENTATION JANUARY 2007

649-7.4 Install: The Contract unit price each for steel strain poles, steel mast arm and monotube assemblies, installed, will include the foundation, blank sign panel, all labor, equipment, miscellaneous materials and hardware necessary for a complete and acceptable installation. The Engineer will supply materials as specified in the Contract Documents.

649-8 Basis of Payment.

Price and payment will be full compensation for all work specified in this Section. Sign panels and/or signal assemblies will be paid for separately.

Payment will be made under:

- | | |
|---------------|---------------------------------|
| Item No. 649- | Mast Arm Assembly - each. |
| Item No. 649- | Steel Monotube Assembly - each. |
| Item No. 649- | Steel Strain Pole - each. |