

# EXPECTED IMPLEMENTATION JANUARY 2010

## 523 PATTERNED/TEXTURED PAVEMENT – QUALIFIED PRODUCTS LIST. (REV 2-12-09) (FA 4-16-09) (1-10)

SUBARTICLE 523-2.1 (of the Supplemental Specifications) is deleted and the following substituted:

**523-2.1 Qualified Products List:** Use only patterned/textured pavement products listed on the Qualified Products List. Meet manufacturer's specifications for all pattern/texture templates, coating and coloring materials. Use only material that is delivered to the job site in sealed containers bearing the manufacturer's original labels.

Material coatings used to achieve the pattern/texture and/or color shall produce an adherent, weather resistant, skid resistant surface capable of resisting deformation to traffic. Surface marking materials must meet the requirements of this Specification and Section 971 with the following exceptions:

1. Color and reflectivity requirements do not apply. Surfaces shall not be made retroreflective.
2. Requirements for minimum set to bear traffic time, do not apply. Do not open to traffic until the coating material has sufficiently dried or cured and is ready to withstand traffic.
3. For thermoplastic materials, the requirements for alkyd based materials only in 971-5.1 and minimum binder content of 971-5.2, do not apply.
4. For thermoplastic materials, the indentation resistance requirements and minimum flashpoint requirements of 971-5.5, do not apply.

Manufacturers seeking approval of their product for inclusion on the QPL must submit an application in accordance with Section 6 along with the following documentation:

1. Manufacturer's specifications and procedures for materials and installation.
2. Manufacturer's Laboratory test data from an independent laboratory verifying the material meets the requirements of this Section.
3. Test data from an independent source verifying that the patterned/textured pavement installed in accordance with the manufacturer's specifications and procedures has been tested in accordance with the ASTM E-274, Skid Resistance of Paved Surfaces using a standard ribbed full Scale Tire at a speed of 40 mph (FN40R), and has a minimum FN40R value of 35.