



## Florida Department of Transportation

RICK SCOTT  
GOVERNOR

605 Suwannee Street  
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.  
SECRETARY

July 7, 2011

Monica Gourdine  
Program Operations Engineer  
Federal Highway Administration  
545 John Knox Road, Suite 200  
Tallahassee, Florida 32303

Re: Office of Design, Specifications  
Section 710  
Proposed Specification: **7100502 Painted Pavement Markings – Alignment.**

Dear Ms. Gourdine:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

These changes were proposed by Chester Henson of the State Roadway Design Office to make specifications consistent with the Design Standards.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via Email to SP965RP or rudy.powell@dot.state.fl.us.

If you have any questions relating to this specification change, please call Rudy Powell, State Specifications Engineer at 414-4280.

Sincerely,

Rudy Powell, Jr., P.E.  
State Specifications Engineer

RP/cah

Attachment

cc: Gregory Jones, Chief Civil Litigation  
Florida Transportation Builders' Assoc.  
State Construction Engineer

**PAINTED PAVEMENT MARKINGS – ALIGNMENT.****(REV 5-26-11)**

SUBARTICLE 710-5.2 (Page 798) is deleted and the following substituted:

**710-5.2 Alignment:** Apply painted stripes that will not deviate more than 1 inch from the stringline on tangents and curves one degree or less. Apply painted stripes that will not deviate more than 2 inches from the stringline on curves greater than one degree. ~~Apply painted edge stripes uniformly, not less than 2 inches or more than 4 inches from the edge of pavement, without noticeable breaks or deviations in alignment or width.~~

Remove and replace at no additional cost to the Department, traffic stripes that deviate more than the above stated requirements.

**PAINTED PAVEMENT MARKINGS – ALIGNMENT.****(REV 5-26-11)**

SUBARTICLE 710-5.2 (Page 798) is deleted and the following substituted:

**710-5.2 Alignment:** Apply painted stripes that will not deviate more than 1 inch from the stringline on tangents and curves one degree or less. Apply painted stripes that will not deviate more than 2 inches from the stringline on curves greater than one degree.

Remove and replace at no additional cost to the Department, traffic stripes that deviate more than the above stated requirements.