



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

May 10, 2013

Monica Gourdine
Program Operations Engineer
Federal Highway Administration
545 John Knox Road, Suite 200
Tallahassee, Florida 32303

Re: Office of Design, Specifications
Section **400**
Proposed Specification: **4002100 Concrete Structures.**

Dear Ms. Gourdine:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

These changes were proposed to correct typographical errors.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to SP965TT or trey.tillander@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4140.

Sincerely,

Signature on file

V. Y. "Trey" Tillander, III, P.E.
Manager State Specifications and Estimates Office

TT/dt

Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

CONCRETE STRUCTURES.**(REV 5-10-13)**

SUBARTICLE 400-21 (Page 386). The heading is deleted and the following substituted:

400-21 Disposition of Cracked Concrete.

SUBARTICLE 400-22.2.5 (Page 393) is deleted and the following substituted:

400-22.2.5 Stay-in-Place Metal Forms: When using stay-in-place metal forms to form the slab of deck girder and beam spans, the volume of concrete will be computed in accordance with the provisions of 400-~~20~~²².2.4 except that the thickness of the slab over the projected plan area of the stay-in-place metal forms will be taken as the thickness shown on the drawings above the top surface of the forms. The concrete required to fill the form flutes will not be included in the volume of concrete thus computed.

CONCRETE STRUCTURES.**(REV 5-10-13)**

SUBARTICLE 400-21 (Page 386). The heading is deleted and the following substituted:

400-21 Disposition of Cracked Concrete.

SUBARTICLE 400-22.2.5 (Page 393) is deleted and the following substituted:

400-22.2.5 Stay-in-Place Metal Forms: When using stay-in-place metal forms to form the slab of deck girder and beam spans, the volume of concrete will be computed in accordance with the provisions of 400-22.2.4 except that the thickness of the slab over the projected plan area of the stay-in-place metal forms will be taken as the thickness shown on the drawings above the top surface of the forms. The concrete required to fill the form flutes will not be included in the volume of concrete thus computed.