

ORIGINATION FORM

Date: May 14, 2014

Originator: Chester A. Henson, P.E.

Contact Information: chester.henson@dot.state.fl.us

Specification Title: **Rumble Strips**

Specification Section, Article, or Subarticle Number: **Section 546-3 and 546-4**

Why does the existing language need to be changed? Added rumble stripes to the specification.

Summary of the changes: Added section for installation of rumble stripes and added revised method of measurement since rumble stripes are measured differently than rumble strips.

Are these changes applicable to all Department jobs? Yes

If not, what are the restrictions?

Will these changes result in an increase or decrease in project costs? Decrease Costs

If yes, what is the estimated change in costs?

With who have you discussed these changes? Specifications, Construction, and Maintenance

What other offices will be impacted by these changes? None

Are changes needed to the PPM, Design Standards, SDG, CPAM or other manual? PPM and BOE

Are all references to external publications current? Yes

If not, what references need to be updated (please include changes in the redline)?

Is a Design Bulletin, Construction Memo, or Estimates Bulletin needed? Joint Estimates and Design Bulletin will be issued.

Contact the State Specifications Office for assistance in completing this form.

Daniel Scheer 850-414-4130 daniel.scheer@dot.state.fl.us

Frances Thomas 850-414-4101 frances.thomas@dot.state.fl.us

Debbie Toole 850-414-4114 deborah.toole@dot.state.fl.us

Andy Harper 850-414-4127 clifton.harper@dot.state.fl.us

Ray Haverty 850-414-4129 ray.haverty@dot.state.fl.us



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

M E M O R A N D U M

DATE: May 22, 2014
TO: Specification Review Distribution List
FROM: Daniel Scheer, P.E., State Specifications Engineer
SUBJECT: Proposed Specification: **5460000 Rumble Strips.**

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Chester Henson to add section for installation of rumble stripes and add revised method of measurement since rumble stripes are measured differently than rumble strips.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or to my attention via e-mail at SP965DS, or daniel.scheer@dot.state.fl.us. Comments received after **June 19, 2014**, may not be considered. Your input is encouraged.

DS/cah
Attachment

RUMBLE STRIPS.
(REV 5-154-14)

SECTION 546 is deleted and the following substituted:

SECTION 546
RUMBLE STRIPS

546-1 Description.

Construct Rumble Strips in accordance with the details shown in the Plans and Design Standards.

546-2 Materials for Raised Rumble Strips.

Construct Raised Rumble Strips using one of the following:

(a) Thermoplastic materials listed on the *Approved Qualified* Products List (QAPL), meeting the requirements of 971-1 and 971-6. Ensure that the material used can be restored to its original dimensions by using a self bonding overlay meeting these requirements. Submit a certified test report to the Engineer indicating that the materials meet all requirements specified.

Before applying thermoplastic materials on portland cement concrete surfaces, apply a primer sealer recommended by the manufacturer.

(b) Any plant-mixed hot bituminous mixture meeting the requirements of a job-mix formula issued by the Department, except open-graded friction course.

Prior to the application of any plant-mixed hot bituminous material, apply a tack coat meeting the requirements of 300-2.3.

The mixture will be accepted on the basis of visual inspection by the Engineer with no further testing required.

546-3 Application.

546-3.1 Raised Rumble Strips: Notify the Engineer before the placement of raised rumble strips. Apply raised rumble strips having well defined edges. Remove and replace any raised rumble strips not meeting the requirements of the Contract Documents at no additional cost to the Department.

Before applying raised rumble strips, remove any material that would adversely affect the bond of the raised rumble strips by a method approved by the Engineer.

Apply raised rumble strips only to dry surfaces, and only when the ambient air and surface temperature is at least 55°F and rising.

546-3.2 Ground-In Rumble Strips: Before the construction of any ground-in rumble strips, demonstrate to the Engineer that the equipment to be used can achieve a depression having well defined edges and a smooth interior finish without snagging or tearing the finished pavement.

Before opening the adjacent lane to traffic, ensure that all debris generated by the grinding process is removed and disposed of daily by vacuum or a method approved by the Engineer. Do not dispose of the debris within the right of way. Do not use the debris generated by the grinding process in recycled asphalt.

Restore any pavement to the satisfaction of the Engineer at no additional cost to the Department, when ground-in rumble strips do not meet the requirements of the Contract Documents.

546-3.3 Ground-In Rumble Stripe: *Construct ground-in rumble strip in accordance with 546-3.2. Apply thermoplastic pavement markings in accordance with Section 711 over the top of the rumble strip as shown in Design Standards, Index No. 518.*

546-4 Method of Measurement.

The quantity of raised rumble strips to be paid for under this Section will be the plan quantity per set, constructed and accepted.

The quantity of ground-in *shoulder* rumble strips to be paid for under this Section will be the plan quantity in miles, constructed and accepted. The plan quantity will be determined based on the roadway length minus bridge lengths for each shoulder on which rumble strips are to be constructed. *No deduction will be made when the skip array is used.*

The quantity of centerline and edge line rumble strip will be the length, in net miles, of ground-in rumble strip, constructed ~~authorized~~ and accepted ~~ably applied~~. No deduction will be made when the skip array is used.

546-5 Compensation.

Prices and payments will be full compensation for all work specified in this Section, including, all cleaning and preparing of surfaces, disposal of all debris, furnishing of all materials, application, curing and protection of all items, protection of traffic, furnishing of all tools, machines and equipment, and all incidentals necessary to complete the work. Final payment will be withheld until all deficiencies are corrected.

Payment will be made under:

- | | |
|-------------------|------------------------------|
| Item No. 546- 71- | Rumble Strip Sets - per set. |
| Item No. 546- 72- | Rumble Strips - per mile. |