



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

May 22, 2014

Chad Thompson
Programs Operations Engineer
Federal Highway Administration
545 John Knox Road, Suite 200
Tallahassee, Florida 32303

Re: State Specifications and Estimates Office
Section **634**
Proposed Specification: **6340203 Span Wire Assembly.**

Dear Mr. Thompson:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

These changes were proposed by Chester Henson to strengthen the wording of the requirement.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to SP965DS or daniel.scheer@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4130.

Sincerely,

Daniel Scheer, P.E.
State Specifications Engineer

DS/cah
Attachment
cc: Florida Transportation Builders' Assoc.
State Construction Engineer

SPAN WIRE ASSEMBLY.**(REV 4-14-14)**

SUBARTICLE 634-2.3 is deleted and the following substituted:

634-2.3 Hardware and Fittings: For ~~U~~utility or Siemens-Martin ~~G~~grade wires, use the connection hardware as specified herein. For installations that use other grades of wire, provide the hardware and fittings indicated in the Plans. Provide only hardware and fittings made of galvanized steel or non-corrosive metal unless the fiberglass insulators specified in 634-2.4 are also required. Provide hardware and fittings of sufficient strength to resist the breaking strength of the wire with which they are used.

Use an alloy steel eyebolt *meeting the requirements of* ASTM F541, Type 2) and a matching heavy hex nut *meeting the requirements of* ASTM A563, Grade C or D), ~~both zinc coated in accordance with ASTM A153, Class C~~, to connect the automatic compression dead-end clamp of the catenary wire ~~and~~ messenger wire to the wood or concrete strain poles. *Eyebolts and hex nuts must be zinc coated in accordance with ASTM A153, Class C.* Sizes of eyebolts, supplied with nuts and washers, are as following: Use a 3/4 inch diameter bolt for maximum of one 7/16 inch diameter catenary (or messenger) wire, or maximum of two 3/8 inch diameter catenary (or messenger) wires. Use a 1 inch diameter bolt for maximum of one 1/2 inch diameter catenary (or messenger) wire, or maximum of two 7/16 inch diameter catenary (or messenger) wires. Use 1-1/4 inch diameter bolt for maximum of two 1/2 inch diameter catenary (or messenger) wires. For two point attachments, connect the messenger wire at the lower attachment location. Do not use thimble eye bolts for these connections.

Only use thimble eye and eye bolts, 3/4 inch in diameter, minimum, to connect the automatic compression dead-end clamps of tether wires to wood or concrete strain poles.

Only use "S" hooks, 5/16 inch in diameter, minimum, when connecting the tether wire to all poles.

Ensure that other hardware and fittings, as required for the attachment of a span wire assembly to support poles or structures, are in accordance with the details shown in the Design Standards.

SPAN WIRE ASSEMBLY.**(REV 4-14-14)**

SUBARTICLE 634-2.3 is deleted and the following substituted:

634-2.3 Hardware and Fittings: For utility or Siemens-Martin grade wires, use the connection hardware as specified herein. For installations that use other grades of wire, provide the hardware and fittings indicated in the Plans. Provide only hardware and fittings made of galvanized steel or non-corrosive metal unless the fiberglass insulators specified in 634-2.4 are also required. Provide hardware and fittings of sufficient strength to resist the breaking strength of the wire with which they are used.

Use an alloy steel eyebolt meeting the requirements of ASTM F541, Type 2 and a matching heavy hex nut meeting the requirements of ASTM A563, Grade C or D, to connect the automatic compression dead-end clamp of the catenary wire and messenger wire to the wood or concrete strain poles. Eyebolts and hex nuts must be zinc coated in accordance with ASTM A153, Class C. Sizes of eyebolts, supplied with nuts and washers, are as following: Use a 3/4 inch diameter bolt for maximum of one 7/16 inch diameter catenary (or messenger) wire, or maximum of two 3/8 inch diameter catenary (or messenger) wires. Use a 1 inch diameter bolt for maximum of one 1/2 inch diameter catenary (or messenger) wire, or maximum of two 7/16 inch diameter catenary (or messenger) wires. Use 1-1/4 inch diameter bolt for maximum of two 1/2 inch diameter catenary (or messenger) wires. For two point attachments, connect the messenger wire at the lower attachment location. Do not use thimble eye bolts for these connections.

Only use thimble eye and eye bolts, 3/4 inch in diameter, minimum, to connect the automatic compression dead-end clamps of tether wires to wood or concrete strain poles.

Only use "S" hooks, 5/16 inch in diameter, minimum, when connecting the tether wire to all poles.

Ensure that other hardware and fittings, as required for the attachment of a span wire assembly to support poles or structures, are in accordance with the details shown in the Design Standards.