

ORIGINATION FORM

Date: May 14, 2014

Originator: Chester A. Henson, P.E.

Contact Information: chester.henson@dot.state.fl.us

Specification Title: **Permanent Tape Traffic Stripes and Markings**

Specification Section, Article, or Subarticle Number: **Section 713-4.3**

Why does the existing language need to be changed? Tapes were originally classified as standard and high performance based on their retroreflectivity and service life. The standard classification was dropped in 2012, leaving only the high performance. Since there is now only one classification for tape and none of the other pavement markings are designated by relative performance, that the high performance designation should be deleted.

Summary of the changes: Dropped the classification high performance since there is only one classification.

Are these changes applicable to all Department jobs? Yes

If not, what are the restrictions?

Will these changes result in an increase or decrease in project costs? No

If yes, what is the estimated change in costs?

With who have you discussed these changes? Specifications, Construction and Maintenance

What other offices will be impacted by these changes? None

Are changes needed to the PPM, Design Standards, SDG, CPAM or other manual? PPM

Are all references to external publications current? Yes

If not, what references need to be updated (please include changes in the redline)?

Is a Design Bulletin, Construction Memo, or Estimates Bulletin needed? No

Contact the State Specifications Office for assistance in completing this form.

Daniel Scheer 850-414-4130 daniel.scheer@dot.state.fl.us

Frances Thomas 850-414-4101 frances.thomas@dot.state.fl.us

Debbie Toole 850-414-4114 deborah.toole@dot.state.fl.us

Andy Harper 850-414-4127 clifton.harper@dot.state.fl.us

Ray Haverty 850-414-4129 ray.haverty@dot.state.fl.us



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

M E M O R A N D U M

DATE: May 22, 2014

TO: Specification Review Distribution List

FROM: Daniel Scheer, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: **7130000 Permanent Tape Traffic Stripes and Markings.**

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Chester Henson to delete the requirements for high performance markings. Traffic tape was previously classified as "standard" or "high performance" based on their retroreflectivity and service life. The standard classification was dropped in 2012 leaving only the high performance. Since there is now only one classification for tape and none of the other pavement markings are designated by relative performance, the high performance designation has been deleted.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or to my attention via e-mail at SP965DS, or daniel.scheer@dot.state.fl.us. Comments received after **June 19, 2014**, may not be considered. Your input is encouraged.

DS/cah
Attachment

PERMANENT TAPE TRAFFIC STRIPES AND MARKINGS.
(REV 5-14-14)

SECTION 713 is deleted and the following substituted:

SECTION 713
PERMANENT TAPE TRAFFIC STRIPES AND MARKINGS

713-1 Description.

Apply permanent tape traffic stripes and markings, in accordance with the Contract documents.

713-2 Materials.

Use only permanent tape traffic stripes and markings materials listed on the **Approved Qualified Products List (QAPL)**, meeting the requirements of 971-1 and 971-7. The Engineer will take random samples of the materials in accordance with the Department's Sampling, Testing and Reporting Guide schedule.

713-3 Equipment.

Use equipment that is mobile and maneuverable to the extent that straight lines can be followed and normal curves can be made in a true arc.

Ensure the mechanical applicator is equipped with film cut-off device and a measuring device that automatically and accumulatively measures the length of each line placed with an accuracy tolerance of plus or minus 2 percent. Tape may be placed by hand on short sections, 500 feet or less if the tolerances in dimensions and in alignment specified in 710-5 are met.

713-4 Application.

713-4.1 General: Remove existing traffic stripes and markings, such that scars or traces of removed markings will not conflict with new stripes and markings by a method approved by the Engineer.

Before applying traffic stripes and markings, remove any material by a method approved by the Engineer that would adversely affect the bond of the traffic stripes.

Apply a primer, sealer or surface preparation adhesive of the type recommended by the manufacturer. Ensure the tape stripes and markings adhere to the pavement surface.

Offset longitudinal lines at least 2 inches from construction joints on portland cement concrete pavement.

Apply traffic stripes or markings only to dry surfaces, and when the ambient air and surface temperature is at least 55°F and rising.

Apply striping to the same tolerances in dimensions and in alignment specified in 710-5. When applying traffic stripes and marking over existing markings, ensure that no more than 2 inches on either end and not more than 1 inch on either side of the existing line is visible.

Apply traffic stripes and markings to the pavement by means approved by the Engineer. The stripes and markings shall be installed immediately following the paving operation. Conduct field testing in accordance with FM 5-541. Take test readings representative of the striping performance. Remove and replace pavement stripes and markings not meeting the requirements of this Section at no additional cost to the Department.

Apply all final pavement markings prior to opening the road to traffic.

713-4.2 Thickness: Apply traffic stripes or markings such that, the stripes or markings will have a thickness as designated on the QAPL for the particular product used.

Measure, record and certify on a Department approved form and submit to the Engineer, the thickness of white and yellow pavement markings in accordance with FM 5-541.

713-4.3 Retroreflectivity: *Apply white and yellow traffic stripes and markings that will attain an initial retroreflectivity of not less than 450 mcd/lx·m² for white markings and not less than 350 mcd/lx·m² for yellow markings. Black portions of contrast tapes and black masking tapes must have a reflectance of less than 5 mcd/lx m².*

~~**713-4.3.1 General:** Black portions of contrast tapes and black masking tapes must have a reflectance of less than 5 mcd/lx·m².~~ Measure, record and certify on Department approved form and submit to the Engineer, the retroreflectivity of white and yellow pavement markings in accordance with FM 5-541.

~~**713-4.3.2 High Performance Markings:** Apply white and yellow traffic stripes and markings that will attain an initial retroreflectivity of not less than 450 mcd/lx·m² for white markings and not less than 350 mcd/lx·m² for yellow markings.~~

713-4.4 Color: Use material meeting the requirements of 971-1.

713-5 Contractor's Responsibility for Notification.

Notify the Engineer prior to the placement of pavement stripes and marking material. Furnish the Engineer with the manufacturer's name and batch numbers of the material to be used. Ensure that the approved batch numbers appear on the material packages.

713-6 Protection of Newly Applied Stripes.

Do not allow traffic onto or permit vehicles to cross onto newly applied traffic stripes and markings until they are sufficiently bonded. Remove and replace any portion of the traffic stripes and markings damaged by passing traffic or from any other cause, at no additional cost to the Department.

713-7 Observation Period.

Longitudinal pavement markings are subject to a 180 day observation period under normal traffic. The observation period shall begin with the satisfactory completion and acceptance of the work.

The longitudinal pavement markings shall show no signs of failure due to blistering, excessive cracking, chipping, discoloration, poor adhesion to the pavement, loss of reflectivity or vehicular damage. The retroreflectivity shall meet the initial requirements of 713-4.3. The Department reserves the right to check the retroreflectivity any time prior to the end of the observation period.

Replace, at no additional expense to the Department, any longitudinal pavement markings that do not perform satisfactorily under traffic during the 180 day observation period.

713-8 Corrections for Deficiencies.

Remove and reapply a 1.0 mile section centered around any deficiency, as determined by the Engineer, at no additional cost to the Department.

713-9 Submittals.

713-9.1 Submittal Instructions: Prepare a certification of quantities, using the Department's current approved form, for each project in the Contract. Submit the certification of quantities and daily worksheets to the Engineer. The Department will not pay for any disputed items until the Engineer approves the certification of quantities.

713-9.2 Contractor's Certification of Quantities: Request payment by submitting a certification of quantities no later than Twelve O clock noon Monday after the estimate cut-off date or as directed by the Engineer, based on the amount of work done or completed. Ensure the certification of quantities consists of the following:

(a) Contract Number, FPID Number, Certification Number, Certification Date and the period that the certification represents.

(b) The basis for arriving at the amount of the progress certification, less payments previously made and less any amount previously retained or withheld. The basis will include a detailed breakdown provided on the certification of items of payment.

713-10 Method of Measurement.

The quantities to be paid for under this Section will be as follows:

(a) The length, in net miles, of 6 inch solid traffic stripe, authorized and acceptably applied.

(b) The total traversed distance in gross miles of 10-30 or 3-9 skip line. The actual applied line is 25% of the traverse distance, for a 1:3 ratio. This equates to 1,320 feet of marking per mile of single line.

(c) The net length, in feet, of all other types of lines and stripes, authorized and acceptably applied.

(d) The area, in square feet, of remove existing markings acceptably removed.

(e) The number of pavement messages, symbols and directional arrows, authorized and acceptably applied.

713-11 Basis of Payment.

Prices and payments will be full compensation for all work specified in this Section, including, all cleaning and preparing of surfaces, furnishing of all materials, application, curing and protection of all items, protection of traffic, furnishing of all tools, machines and equipment, and all incidentals necessary to complete the work. Final payment will be withheld until all deficiencies are corrected.

Payment will be made under:

Item No. 713-102- Permanent Tape ~~(High Performance)~~.