

# EXPECTED IMPLEMENTATION JULY 2010

## 330 HOT BITUMINOUS MIXTURES – GENERAL CONSTRUCTION REQUIREMENTS.

(REV 1-26-10) (FA 2-2-10) (7-10)

SUBARTICLE 330-12.3 (of the Supplemental Specifications) is deleted and the following substituted:

**330-12.3 Cross Slope:** Construct a pavement surface with cross slopes in compliance with the requirements of the Contract Documents. Furnish an electronic level with a length of 4 feet and an accuracy of 0.1 degree, approved by the Engineer for the control of cross slope. Make this electronic level available at the jobsite at all times during paving operations.

**330-12.3.1 Quality Control Requirements:** Calibrate the electronic levels a minimum of once per day before any paving operation, in accordance with manufacturer's instructions.

Compare the Quality Control level with the Verification level before any paving operation, and at any time directed by the Engineer. If the comparison between the Quality Control and Verification levels is within the comparison tolerance of plus or minus 0.2%, the Quality Control level is considered to compare favorably and can be used for measurement and acceptance of cross slopes. If the levels do not compare favorably, perform a second comparison using another calibrated electronic level (FDOT or Contractor) for resolution. If this resolution level compares favorably with the Quality Control level, the Quality Control level is considered to be verified. If the second level does not compare favorably with the Quality Control level, discontinue the use of the Quality Control electronic level and obtain another approved electronic level that meets the requirements of this specification. Regardless of the comparison analysis outcome, the Contractor assumes all risk associated with placing the pavement at the correct cross slope.

Measure the cross slope of the compacted pavement surface by placing the level at the center location of a lane and perpendicular to the roadway centerline. Record all the measurements to the nearest 0.1% on an approved form and submit to the Engineer for documentation.

1. Tangent Sections: Measure the cross slope per lane at a minimum frequency of one measurement every 100 feet. Calculate the absolute deviation of cross slope at each measurement and then average the absolute deviation of ten consecutive cross slope measurements. The absolute deviation is the positive value of a deviation. When the average absolute deviation cross slope is consistently within the acceptance tolerance as shown in Table 330-2 and upon the approval of the Engineer, the frequency of the cross slope measurements can be reduced to one measurement every 200 feet during paving operations.

2. Superelevated Sections: Measure the cross slope every 100 feet per lane within the length of full superelevation. Calculate the absolute deviation of each measurement and then average the absolute deviation of ten consecutive cross slope measurements. For every transition section, measure the cross slope at control points identified in the plans, or if not shown in the plans, at a control point at the location of 0.0% cross slope and calculate the absolute deviation. For curves where the length of full superelevation is less than 250 feet, measure the cross slope at the beginning point, midpoint and ending point of the fully superelevated sections, calculate the absolute deviation, and average . When the number of

# EXPECTED IMPLEMENTATION JULY 2010

measurements is less than ten and the length of full superelevation is greater than 250 feet, average the absolute deviation of all measurements.

If the average absolute deviation of the cross slope measurements falls outside the acceptance tolerance, as shown in Table 330-2, stop the paving operations and make adjustments until the problem is resolved to the satisfaction of the Engineer. If an individual cross slope deviation falls outside the acceptance tolerance as shown in Table 330-2, make corrections in accordance with 330-12.5 only to cover the deficient area for the structural course at no cost to the Department. For pavement with multiple layers, the deficient areas for the structural course may be left in place, upon the approval of the Engineer. Complete corrections before placement of the final design surface layer (Type SP layer or friction course layer), unless stated otherwise in the plans, or as determined by the Engineer. For friction course layers, make corrections in accordance with 330-12.5.

The limits of deficient areas requiring correction may be verified and adjusted with more accurate measurement methods, including survey instruments, upon approval by the Engineer at no cost to the Department.

Should the Contractor wish to have any corrections waived, submit a request to the Engineer for approval. The Engineer may waive the corrections at no reduction in payment if the deficiencies are sufficiently separated so as not to affect the overall traffic safety, surface drainage and ride quality characteristics of the pavement and the corrective action would unnecessarily mar the appearance of the finished pavement.

For intersections, tapers, crossovers, transitions at the beginning and end of the project, bridge approaches and similar areas, adjust the cross slope to match the actual site conditions, or as directed by the Engineer.

Roadway Feature	Individual Absolute Deviation	Average Absolute Deviation
Tangent section (including turn lanes)	0.4%	0.2%
Superelevated curve	0.4%	0.2%
Shoulder	0.5%	0.5%

In the event that the distance between two edges of deficient areas is less than 100 feet, the correction work shall include the area between the deficient sections.

**330-12.3.2 Verification:** The Engineer will verify the Contractor's cross slope measurements by randomly taking a minimum of ten cross slope measurements per lane per mile in tangent sections, control points in transition sections, and a minimum of three cross slope measurements on fully superelevated sections over a day's production. The Engineer will measure the cross slope of the compacted pavement surface by placing the level at the center location of a lane and perpendicular to the roadway centerline. If the average absolute deviation or an individual cross slope deviation falls outside of the acceptance tolerance as shown in Table 330-2, immediately make a comparison check at the QC test locations to verify the QC measurements in the questionable section. If the comparisons are beyond the acceptable comparison tolerance in accordance with 330-12.3.1, stop the paving operations until the problem is resolved to the satisfaction of the Engineer. Correct any cross slope not meeting the individual deviation acceptance tolerance in accordance with 330-12.5 at no cost to the

# EXPECTED IMPLEMENTATION JULY 2010

Department. The Engineer reserves the right to check the pavement cross slope at any time by taking cross slope measurements at any location.

D

R

A

F

T