



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.
SECRETARY

February 14, 2013

Monica Gourdine
Program Operations Engineer
Federal Highway Administration
545 John Knox Road, Suite 200
Tallahassee, Florida 32303

Re: Office of Design, Specifications
Section **353**
Proposed Specification: **3531100 Concrete Pavement Slab Replacement.**

Dear Ms. Gourdine:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

These changes were proposed by Rudy Powell of the State Construction Office to decrease the potential for contract disputes on determining the pay quantity by changing the method of measurement from "pavement design thickness" to "thickness of the removed slab".

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to SP965TT or trey.tillander@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4140.

Sincerely,

Signature on file

V. Y. "Trey" Tillander, III, P.E.
State Specifications Engineer

TT/dt

Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

CONCRETE PAVEMENT SLAB REPLACEMENT**(REV ~~12-27-12~~-14-13)**

ARTICLE 353-11 (Page 351) is deleted and the following substituted:

353-11 Method of Measurement.

The *pay* quantity ~~to be paid for~~ will be the volume, in cubic yards, of concrete placed and accepted *determined by calculation*. The quantity will be calculated *using on the basis of* field-measured horizontal dimensions and ~~pavement design~~ thickness *of the removed slab*. ~~No additional compensation will be allowed for additional concrete required to bring the proposed concrete slab up to finished grade.~~

**CONCRETE PAVEMENT SLAB REPLACEMENT
(REV 2-14-13)**

ARTICLE 353-11 (Page 351) is deleted and the following substituted:

353-11 Method of Measurement.

The pay quantity will be the volume, in cubic yards, of concrete placed and accepted determined by calculation. The quantity will be calculated using field-measured horizontal dimensions and thickness of the removed slab.