



## Florida Department of Transportation

**RICK SCOTT**  
**GOVERNOR**

605 Suwannee Street  
Tallahassee, FL 32399-0450

**ANANTH PRASAD, P.E.**  
**SECRETARY**

January 8, 2013

Monica Gourline  
Program Operations Engineer  
Federal Highway Administration  
545 John Knox Road, Suite 200  
Tallahassee, Florida 32303

Re: Office of Design, Specifications  
Section **470**  
Proposed Specification: **4701202 Timber Structures.**

Dear Ms. Gourline:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

These changes were proposed by Paul Vinik of the State Materials Office, to correct some minor editorial changes.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to SP965TT or [trey.tillander@dot.state.fl.us](mailto:trey.tillander@dot.state.fl.us).

If you have any questions relating to this specification change, please call me at 414-4140.

Sincerely,

V. Y. "Trey" Tillander, III, P.E.  
State Specifications Engineer

TT/cah

Attachment

cc: Florida Transportation Builders' Assoc.  
State Construction Engineer

**TIMBER STRUCTURES.**  
**(REV 11-13-12)**

SUBARTICLE 470-12.2 (Page 652) is deleted and the following substituted:

**470-12.2 CCA, ACQ-D, ~~CA-B~~, and CA-C, Treated Timber Structures:** Use the fasteners and connectors as described in the following table:

TABLE – HARDWARE REQUIREMENTS FOR TREATED TIMBER		
Environmental condition where structure will be located	Fasteners	Connectors
Permanent wood foundations and/or where salt spray is prevalent	304 or 316 Stainless Steel	304 or 316 Stainless Steel
Structures that will be exposed to standing water or rainwater	304 or 316 Stainless Steel	304 or 316 Stainless Steel
Structures that will be situated indoors and remain dry in service	304 or 316 Stainless Steel  Hot-dipped galvanized fasteners meeting ASTM A-153 requirements	304 or 316 Stainless Steel  Hot-dipped galvanized connectors meeting the requirements of ASTM A-653 Class G185 sheet or better
Do not use aluminum in direct contact with treated wood.		

**TIMBER STRUCTURES.**  
**(REV 11-13-12)**

SUBARTICLE 470-12.2 (Page 652) is deleted and the following substituted:

**470-12.2 CCA, ACQ-D, and CA-C, Treated Timber Structures:** Use the fasteners and connectors as described in the following table:

TABLE – HARDWARE REQUIREMENTS FOR TREATED TIMBER		
Environmental condition where structure will be located	Fasteners	Connectors
Permanent wood foundations and/or where salt spray is prevalent	304 or 316 Stainless Steel	304 or 316 Stainless Steel
Structures that will be exposed to standing water or rainwater	304 or 316 Stainless Steel	304 or 316 Stainless Steel
Structures that will be situated indoors and remain dry in service	304 or 316 Stainless Steel  Hot-dipped galvanized fasteners meeting ASTM A-153 requirements	304 or 316 Stainless Steel  Hot-dipped galvanized connectors meeting the requirements of ASTM A-653 Class G185 sheet or better
Do not use aluminum in direct contact with treated wood.		