



## Florida Department of Transportation

RICK SCOTT  
GOVERNOR

605 Suwannee Street  
Tallahassee, FL 32399-0450

ANANTH PRASAD, P.E.  
SECRETARY

December 9, 2013

Chad Thompson  
Programs Operations Engineer  
Federal Highway Administration  
545 John Knox Road, Suite 200  
Tallahassee, Florida 32303

Re: State Specifications and Estimates Office  
Section **931**  
Proposed Specification: **9310306 Metal Accessory Materials for Concrete Pavement and Concrete Structures. REVISED**

Dear Mr. Thompson:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification. These changes were previously submitted to your office and approved on November 26, 2013.

Additional changes were requested by the State Construction office. These changes are **highlighted** in the attached document.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to SP965DS or daniel.scheer@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4130.

Sincerely,

Signature on file

Daniel Scheer, P.E.  
State Specifications Engineer

DS/dt

Attachment

cc: Florida Transportation Builders' Assoc.  
State Construction Engineer

**METAL ACCESSORY MATERIALS FOR CONCRETE PAVEMENT AND  
CONCRETE STRUCTURES.**

(REV ~~9-19-13~~ 12-9-13)

SUBARTICLE 931-3.6 is deleted and the following substituted:

**931-3.6 Materials:** The wire for the welded assembly shall be in accordance with all applicable requirements of ASTM A82.

After fabrication, apply one coat of alkyd primer meeting the material requirements of SSPC Paint 25 ~~to all exposed surfaces of the assembly~~. Apply the primer in accordance with the manufacturer's recommendations.

**METAL ACCESSORY MATERIALS FOR CONCRETE PAVEMENT AND  
CONCRETE STRUCTURES.**

**(REV 9-19-13)**

SUBARTICLE 931-3.6 is deleted and the following substituted:

**931-3.6 Materials:** The wire for the welded assembly shall be in accordance with all applicable requirements of ASTM A82.

After fabrication, apply one coat of alkyd primer meeting the material requirements of SSPC Paint 25 to all exposed surfaces of the assembly. Apply the primer in accordance with the manufacturer's recommendations.