

1020914 MAINTENANCE OF TRAFFIC
COMMENTS FROM INTERNAL/INDUSTRY REVIEW

Charles Boyd
414-

charles.boyd@dot.state.fl.us

Comments: (11-17-14, Internal)

Suggest the added/deleted **highlighted** text.

~~→ → Ensure that the complete unit is painted DOT yellow (Fed. Std. 595b, No. 13538). Stripe the rear-facing of the cartridge in the operating position with the alternating 6 inch white and 6 inch safety orange 45 degree striping to form an inverted "V" at the center of the unit and slope down and toward the outside of the unit, in both directions from the center. In the raised position, place at least the same square footage of striping on the bottom of the cartridge as placed on the rear-facing cartridge in the open position. Use Type III retroreflectorized sheeting for striping. Install alternating black and yellow or white and orange sheeting on the rear of the TM4 truck-mounted or trailer-mounted attenuator, in both the operating and raised and lowered positions. The sheeting shall consist of 4 or 6 inch stripes installed to form chevrons that point upward. Use Type III (workzone) or Type IV sheeting. All sheeting except black shall be retroreflective, except Black.~~

Response: Language is clear as stated.
No changes made.

Ben Lewis
414-4197
ben.lewis@dot.state.fl.us

Comments: (11-26-14)

The language as written is unclear. An alternative may be: "Install either alternating black with yellow or white with orange sheeting on the rear of trailer mounted attenuators and on truck mounted attenuators, in both the operating and raised position." (See **highlighted** changes below.)

~~the unit and slope down and toward the outside of the unit, in both directions from the center. In the raised position, place at least the same square footage of striping on the bottom of the cartridge as placed on the rear-facing cartridge in the open position. Use Type III retroreflectorized sheeting for striping. Install either alternating black and with yellow or white and with orange sheeting on the rear of trailer-mounted attenuators and on truck-mounted attenuators, in both the operating and raised position. Use Type III (work-zone) or Type IV sheeting consisting of 4 or 6 inch wide stripes installed to form chevrons that point upward. All sheeting except black shall be retroreflective.~~

Response: Agree. Suggested edits will be made.
Changes made.
