

EXPECTED IMPLEMENTATION JULY 2015

D

700 HIGHWAY SIGNING.
(REV 10-29-14) (FA 1-16-15) (7-15)

SUBARTICLE 700-1.2.2 is deleted and the following substituted:

700-1.2.2 Concrete: Use concrete meeting the requirements of Section 346. Obtain concrete from a plant that is listed on the Department's Production Facility Listing. Producers seeking inclusion on the list shall meet the requirements of Section 105.

R

SUBARTICLE 700-1.3 is deleted and the following substituted:

700-1.3 Sign Fabrication Requirements: Obtain multi-post and overhead sign structures from a facility that is listed on the Department's Production Facility Listing. Producers seeking inclusion on the list shall meet the requirements of Section 105.

SUBARTICLE 700-2.1.3 is deleted and the following substituted:

A

700-2.1.3 Foundation: Construct foundations in accordance with the applicable Design Standards. The Contractor may use precast foundations in augured or excavated holes a minimum of 12 inches larger than each axis dimension of the precast foundation. Obtain precast foundations from a plant that is currently on the Department's Production Facility Listing. Producers seeking inclusion on the list shall meet the requirements of Section 105. The holes must be clean and without loose material. Temporary casing will be required if the soil is unstable. Fill the void around the precast foundation with flowable fill meeting the requirements of Section 121 or use clean sand placed using hydraulic methods.

SUBARTICLE 700-2.2.1.1 is deleted and the following substituted:

F

700-2.2.1.1 General: Obtain reinforcing steel, multi-post and overhead sign structures from a fabrication facility that is listed on the Department's Production Facility Listing. Producers seeking inclusion on the list shall meet the requirements of Section 105.

Only use structural steel, including bolts, nuts, and washers, that have been hot dip galvanized or metalized after fabrication. Perform hot dip galvanizing in accordance with Section 962 and metalizing in accordance with Section 562.

For galvanized steel members, meet the general requirements of Section 962. Obtain galvanized steel from a fabrication facility that is listed on the Department's Production Facility Listing. Producers seeking inclusion on the list shall meet the requirements of Section 105.

T

Use a galvanizing compound as specified in Section 975. Use a galvanizing repair compound listed on the APL for large areas as defined in Section 975.