

# EXPECTED IMPLEMENTATION JULY 2017

## 710 PAINTED PAVEMENT MARKINGS.

(REV 8-2-16) (FA 10-24-16) (7-17)

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

**710-4.1.1 Painted Pavement Markings (Final Surface):** On concrete surfaces or newly constructed asphalt without rumble striping, the painted pavement markings (final surface) will include one application of standard paint and one application of Class B retroreflective pavement markers applied to the final surface.

On newly constructed asphalt with rumble striping, apply two applications of standard paint and one application of Class B retroreflective pavement markers. Additionally, for center line rumble striping installations, install Class D retroreflective pavement markers with the first application of standard paint. Remove Class D markers prior to grinding, and install Class B retroreflective pavement markers in an unground area after grinding. The second application of standard paint must be applied within 24 hours of each day's grinding operation.

Do not apply final surface paint for bicycle arrows or bicycle messages, 24 inch longitudinal bars in special emphasis crosswalks, or route shields where preformed thermoplastic will be applied.

Install all retroreflective pavement markers in accordance with Design Standards, Index Nos. 17352 and 17345, prior to opening the road to traffic.

Temporary retroreflective pavement markers must meet the requirements of Section 102.

Permanent retroreflective pavement markers must meet the requirements of Section 706.