

702 WET WEATHER PAVEMENT MARKINGS.
(REV 9-5-13) (FA 10-23-13) (7-14)

SUBARTICLE 702-4.2 is deleted and the following substituted:

702-4.2 Thickness and Dimensions of Markings: For flat thermoplastic markings provide a thickness of 0.100 to 0.150 inches when measured above the pavement surface.

Measure, record and certify on a Department approved form and submit to the Engineer, the thickness of white and yellow pavement markings in accordance with FM 5-541.

The Engineer will verify the thickness of the pavement markings in accordance with FM 5-541 within 30 days of receipt of the Contractor's certification.

ARTICLE 702-7 is deleted and the following substituted:

702-7 Observation Period and Contractor's Warranty.

Longitudinal pavement markings are subject to a 180 day observation period under normal traffic. The observation period will begin with the satisfactory completion and acceptance of the pavement marking work.

The longitudinal pavement markings shall show no signs of failure due to blistering, excessive cracking, chipping, discoloration, poor adhesion to the pavement, loss of reflectivity or vehicular damage. The retroreflectivity shall meet the initial requirements of 702-4.4. The Department reserves the right to check the retroreflectivity anytime prior to the end of the observation period.

Replace, at no expense to the Department, any longitudinal pavement markings that do not perform satisfactorily under traffic during the 180 day observation period.