



Maximum spacing between cones and tubular markers shall be 25'  
 Maximum spacing between Type I or Type II barricades or vertical panels or drums shall be based on the speed limit as follows:  
 15' for 25 MPH; 30' for 30 - 40 MPH;  
 50' for 45 MPH and greater.

When Other Construction Or Maintenance Operations Occur Within 1 mile, Signs 1 To Be Omitted And Signing To Be Coordinated In Accordance With Index No. 600.

Cones Or Tubular Markers At 25' Centers For First 250' Thereafter At 50' Centers Or Either Type I Or Type II Barricades Or Vertical Panels Or Drums At 50' Centers For First 25' Thereafter At 100' Centers.

### GENERAL NOTES

- All vehicles, equipment, workers (except flaggers) and their activities are restricted at all times to one side of the roadway.
- If the work operation does not exceed 60 minutes, traffic control will be in conformance with Index No. 607.
- When four or more work vehicles enter the through traffic lanes in a one hour period or less, the advanced FLAGGER sign shall be substituted for the WORKERS sign. For location of flaggers and FLAGGER signs, see Index No. 603.
- The first two warning signs shall have a 18" x 18" (min.) orange flag and a Type B light attached and operating at all times. Mesh signs may be used for (Daylight Only) operations. Type B Lights and Orange Flags are not required.
- The WORKERS legend sign may be substituted for the symbol sign.
- All signs shall be post mounted if the work operation time exceeds 12 hours.
- $L \text{ (min.)} = \frac{WS^2}{2}$  for speeds  $\geq 45$  mph  
 $\frac{WS^2}{120}$  for speeds  $\leq 40$  mph  
 Where:  
 W = Width of shoulder in feet, 8' minimum.  
 S = Posted speed limit (mph)
- Arrows denote direction of traffic only and do not reflect pavement markings.
- Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
- WORKERS sign to be removed or fully covered when no work is being performed.
- When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ indexes.
- For general TCZ requirements and additional information refer to Index No. 600.

### TYPICAL APPLICATIONS

Utility Work  
 Culvert Extensions  
 Side Slope Work  
 Guardrail Work  
 Landscaping Work  
 Cleaning Drainage Structures  
 Reworking Ditches  
 Sign Installation And Maintenance  
 Shoulder Repair

### CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCR OACH THE AREA CLOSER THAN 15' BUT NOT CLOSER THAN 2' TO THE EDGE OF PAVEMENT

### SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only). (Tubular Markers May Be Used During Daylight Only. Cones May Be Used - See Index 600).
- Work Zone Sign

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
 ROAD DESIGN

### TRAFFIC CONTROL THROUGH WORK ZONES TWO-LANE, TWO-WAY • RURAL DAY OR NIGHT OPERATIONS

DESIGNED BY	DATE	APPROVED BY
GW	08/01	[Signature]
DRAWN BY	DATE	SCALE
GW	08/01	1 of 1
CHECKED BY	DATE	INDEX NO.
GW	08/01	602