



2012 Highway Safety Manual Calibration Factors

FDOT Segment Calibration Factors		
Segment Type	Abbreviation	Calibration Factor (C_x)
Rural 2-lane, 2-way Undivided Roadway	R2U	1.00
Rural 4-lane Divided Roadway	R4D	0.68
Urban 2-lane Undivided Roadway	U2U	1.02
Urban 3-lane Roadway with a Center TWLTL	U32LT	1.04
Urban 4-lane Undivided Roadway	U4U	0.73
Urban 4-lane Divided Roadway	U4D	1.63
Urban 5-lane Roadway with a Center TWLTL	U52LT	0.70
FDOT Intersection Calibration Factors		
Intersection Type	Abbreviation	Calibration Factor (C_x)
Rural 2-lane 3-Leg Stop-Controlled Intersection	R23ST	1.30
Rural 2-lane 4-Leg Stop-Controlled Intersection	R24ST	0.90
Rural 2-lane 4-Leg Signalized Intersection	R24SG	1.00
Rural Multilane 4-Leg Signalized Intersection	RM4SG	1.00
Urban 3-Leg Stop-Controlled Intersection	U3ST	0.98
Urban 3-Leg Signalized Intersection	U3SG	1.56
Urban 4-Leg Signalized Intersection	U4SG	1.00