#### Fiber Reinforced Polymer (FRP) Composites



#### Gevin McDaniel, P.E. Roadway Design Standards Administrator & Chase Knight, PhD Composite Materials Research Specialist

# **Topics Covered**

- Overview of FRP Composites
- Currently Available National Specifications
- FDOT Design Criteria and Specifications
- Acceptable FDOT Applications
- Research on FRP Composites
- District 7 Demonstration Project
- Chase Knight, PhD Usage (Characteristics/Durability)
- Questions



# FRP Overview: What is FRP?

#### General Composition



# Fiber Reinforced Polymer



# **FRP Overview: Fibers**

- Common Fiber Types:
  - Aramid
    - Extremely sensitive to environmental conditions
  - ✓ Glass (Most Widely Used)
    - Subject to creep under high sustained loading
    - Subject to degradation in alkaline environment
  - Carbon
    - Premium Cost
  - ✓ Basalt
    - The future of FRP fibers?



# **FRP Overview: Fibers**

#### Used in many different forms:




Short Fibers



Long Fibers



**Chopped Fibers** 



Woven Fibers



#### • Two Categories:

Thermoset Resins (most common for structural uses)

- Liquid state at room temperature prior to curing
- Impregnated into reinforcing fibers prior to heating
- Chemical reaction occurs during heating/curing
- Solid after heating/curing; Can't be reversed/reformed
- Thermoplastic Resins
  - Solid at room temperature (recycled plastic pellets)
  - Heated to liquid state and pressurized to impregnate reinforcing fibers
  - Cooled under pressure; Can be reversed/reformed

- Common Thermoset Resin Types
  - Polyester
    - Lowest Cost
  - ✓ Vinyl ester
    - Industry Standard
  - Polyurethane
    - Premium Cost
  - 🗸 Ероху
    - Highest Cost
    - Commonly used in aerospace applications



#### Polyesters

- Advantages:
  - Easy to use
  - Lowest cost of resins available
- Disadvantages:
  - Sensitive to UV degradation
  - Only moderate mechanical properties



#### Vinyl esters

- Advantages:
  - Very high chemical/environmental resistance
  - Higher mechanical properties than polyesters
- Disadvantages:
  - Sensitive to heat
  - Higher cost than polyesters



#### Polyurethanes

#### Advantages:

- Higher strength and flexibility than vinyl esters
- Very high chemical/environmental resistance
- Higher mechanical properties than vinyl esters
- Disadvantages:
  - Higher cost than vinyl esters (about 1.5 x)



#### Epoxies

#### Advantages:

- High mechanical and thermal properties
- High moisture resistance
- Long working times available
- High temperature resistance
- Disadvantages:
  - More expensive than polyurethanes
  - Critical mixing/Consistency
  - Corrosive handling



- Manufacturing Processes
  - Predominate Processes
    - Pultrusion
    - Vacuum Infusion
  - Other Processes







Pultrusion Processing:

- Linear, continuous process
- Reinforcing (Roving & Mats) saturated with resin
- Pulled through heated die
- Chemical reaction occurs as it cures (Polymerization)
- The resin saturated reinforcements exit the die in a solid state and in the form of the cross section of the die.
- Types of products produced:
  - Structural shapes w/ constant cross-sections
  - GFRP/CFRP reinforcing bars & CFRP prestressing bars



# <section-header>FRP Overview: Processes • Pultrusion Processing: Virgs Guide Plane Fesin Virgs Surfacing & Extracting & Ex





Courtesy of: Creative Pultrusions, Inc.

Continuous Strand Mats: Reinforcements in any direction; consistent along the length of the member.



• Pultruded hollow piles








Courtesy of: Creative Pultrusions, Inc. 16

#### Various Pultruded Structural Shapes




Courtesy of: Creative Pultrusions, Inc.



• Pultruded GFRP/CFRP reinforcing bars and dowels


sian Train




- Vacuum Infusion (VIP)
  - Reinforcing laid dry into the mold
  - Vacuum is pulled before resin is introduced
  - Resin is then sucked into the laminate via distributed tubing
  - ✓ Types of products:
    - Structural shapes:
      - Uniform cross-sections
      - Non-uniform cross-sections



#### Vacuum Infusion (VIP)



Benefit of VIP: Reinforcing fibers oriented in any direction at specific and targeted locations.








• Variable shape and size of VIP structural members


2



- Other Processes
  - Bladder Molding
  - Compression Molding
  - Thermoplastic Extrusion
  - Filament winding
  - ✓ Wet Layup
  - Others



Bladder Molding



Wet Layup



- LRFD Design
   Specification for FRP
   Pultruded Structures
  - Structural shapes
  - Connections
  - Prefabricated building products
- Symmetric and balanced glass fiber reinforcing only

Pre-Standard for Load & Resistance Factor Design (LRFD) of Pultruded Fiber Reinforced Polymer (FRP) Structures (Final)

Submitted to: American Composites Manufacturers Association (ACMA)

November 9, 2010





- ANSI Code of Standard Practice
- Pultruded FRP Structures
- Recommendations for:
  - Construction Contract Documents
  - Fabrication
  - Installation



ANSI/ACMA/PIC - Standard Practice - 2011

#### CODE OF STANDARD PRACTICE

Industry Guidelines for Fabrication and Installation of Pultruded FRP Structures


FIRST EDITION



Published by American Composites Manufacturers Association



- For the design and construction of concrete bridge decks and railings reinforced with GFRP reinforcing bars.
- For GFRP bars only:
  - Deformed or Sand Coated only
  - See additional limitations





- For the analysis and design of concrete-filled FRP tubes (CFFT) for use as structural components in bridges
- For CFFT use as:
  - ✓ Beams
  - Arches
  - ✓ Columns
  - ✓ Piles





#### LRED GUIDE SPECIFICATIONS DESIGN OF CONCRETE-FILLED FRP TUBES FOR FLEXURAL AND AXIAL MEMBERS

AMERICAN ASSOCIATION OF STATE HIGHWAY AND RANSPORTATION OFFICIALS

In Amazin Contraction of The second bios (SIRAC) 2001

ACI 440R-07

Report on Fiber-Reinforced Polymer (FRP) Reinforcement for Concrete Structures

Reported by ACI Committee 440



- ACI 440 Series:
  - FRP Reinforcement for Concrete

ASTM

- Materials, Design and Construction Specifications
- ASTM is currently being developed to replace the materials specifications for FRP reinforcing

#### **FDOT Specifications**

- FRP Composite Structural Shapes:
  - Current Section 973: "Structural Plastics"
  - Revised Section 973: FRP Composite Structural Shapes
    - Thermoset Pultruded Structural Shapes
    - Thermoset Vacuum Infusion Processed (VIP) Structural Shapes
    - Thermoplastic Structural Shapes
      - Unreinforced
      - Reinforced with GFRP Bars





#### **FDOT Specifications**

• FRP Composite Reinforcing:

- ✓ Dev. 932: FRP Reinforcing Bar (2014)
- ✓ Dev. 933: FRP Strand (2014)
- ✓ Dev. 400, 415, 450, 105 for FRP Reinforcing (2014)

The draft versions currently reference ACI 440 and modifies it to be incompliance with the latest draft of the ASTM. Will reference the new ASTM once ACI 440 is replaced.



**New** Materials Manual Chapter 12

- Included in the July 2014 Workbook
- Requirements for Quality Control (QC) Programs for FRP Composite Producers
- Must obtain FRP Composites from a producer that is currently on the list of Producers with Accepted Quality Control (QC) Programs for Fiber Reinforced Polymer (FRP) Composites
- All FRP Composites must meet the minimum requirements of the applicable material specifications



#### New Structure Manual, Volume 4

- Scheduled for release with the 2015 Structures Manual
- Guidance on acceptable uses for FRP Composites
- Guidance on how to incorporate FRP Components into the Contract Documents
- Provides Design Guidelines and appropriate references to the applicable National Specifications
- Guidance for preparation of Specifications Package



## **FRP Overview: Applications**

#### Global Applications

- Marine transportation components
- Architectural Cladding components
- Aerospace transportation and weapons components
- Automotive components
- Energy Sector components(wind turbines)
- Static Structural Components(Buildings/Bridges)



# **FDOT FRP Initiatives:**

Structural Shapes

- ✓ Fender System Piles, Wales, and Catwalks
- Composite Beams
  - Hillman Beam D7 Project
- Concrete Reinforcing Invitation to Innovation
  - Reinforcing bars
  - Pre-stressing strands
  - External reinforcing (maintenance)



## FDOT FRP Initiatives:

Fender System Piles and Wales

- ✓ FDOT 471 & 973 spec.
- New Approved Fabricators List requirements through MM 12.1 (July 2014)
- Revised SDG Section 3.14 (Jan 2015)
- New Structure Detailing Manual Chapter 24 (Jan 2015)

Courtesy of: Creative Pultrusions, Inc.


Zxpo

# FDOT FRP Initiatives:

#### Composite Beams

#### Hillman Composite Beam

- constructed as a composite of three materials: steel strands, concrete, and fiber reinforced polymer
- materials are arranged in a manner that the materials act as what would traditionally be separate structural elements
- District 7 (Halls River Project)




## **D7 Halls River Project**

Demonstration Project in District 7:


- CR490A bridge replacement over Halls River
- Bridge Length = 185'-10" total
- 5 spans @ 37'-2"
- Overall Bridge Width = 56'-9 3/4"
- ✓ Hybrid Composite Beams (Hillman Beam) = 11 beams @ 5'-3"
- ✓ 24" Prestressed concrete piles w/CFRP strands and spirals
- Concrete seawalls replacement using GFRP & CFRP reinforcement
- Phased construction
- Extremely aggressive environment for both superstructure & substructure



#### **D7 Halls River Project**



#### **D7 Halls River Project**



## **FDOT FRP Initiatives:**

- Concrete Repair (Maintenance)
  - Extension of service life
  - ✓ Near Surface Reinforcing
    - Carbon Fiber Fabric Wraps
    - Near Surface Reinforcing Bars







#### Fiber Reinforced Polymer (FRP) Reinforcing Bars and Strands



# FDOT FRP Initiatives:

#### Concrete Reinforcing

#### Reinforcing Bars (GFRP and/or CFRP)

- Approach Slabs
- Bridge Decks and Bridge Deck overlays
- Cast-in-Place Flat Slab Superstructures
- Pile Bent Caps not in direct contact with water
- Pier Columns and Caps not in direct contact with water
- Retaining Walls, Noise Walls, Perimeter Walls
- Pedestrian/Bicycle Railings
- Bulkheads
- MSE Wall Panels
- Wall Copings
- Drainage Structures
- Concrete Sheet Piles










## **FDOT FRP Initiatives:**

- Concrete Pretensioning
  - Pre-stressing strands(CFRP)
    - Pre-stressed Concrete Piles (with CFRP spirals)
    - Pre-stressed Concrete Sheet Piles





## Research

#### M.H. Ansley Structures Research Center

- Recent Testing on FRP Composites
  - ✓ GFRP Reinforced Thermoplastic Piles and Wales
  - ✓ VIP Composite Bridge Decking
  - Pultruded Light Poles
    - Breakaway Pole Bases
  - Prestressed Concrete Piles using CFCC
  - Post Tensioned Box Girder using CFCC
  - Mast Arm/Light Pole repair using CFRP Wraping








#### Research



## Research

- Leading Researcher on FRP Reinforcing and Prestressing
  - Dr. Brahim Benmokrane, P. Eng., FACI, FCSCE, FIIFC, FCAE, FEIC
    - FRP-ACI Committee Member
    - Professor of Civil Engineering-Fellow of the Royal Society of Canada
    - Tier-1 Canada Research Chair in Advanced Composite Materials for Civil Structures
    - NSERC/Industry Research Chair in Innovative FRP Reinforcement for Concrete Infrastructure
    - Director, Quebec-FQRNT Research Centre on Concrete Infrastructure (CRIB)





#### Characteristics

#### PROS

- It is highly resistant to chloride ion and chemical attack
- Its tensile strength is greater than that of steel yet it weighs only one quarter as much
- It is transparent to magnetic fields and radar frequencies
- GFRP has low electrical and thermal conductivity


#### ✓ CONS

- Due to its inelastic behavior design codes significantly reduce the allowable stress capacity
- Due to the manufacturing processes the industry is undergoing progressive standardization
- Storage and handling requirements for FRP reinforcing on the construction site can be more restrictive due to FRP's susceptibility to damage by overexposure to UV light, improper cutting or aggressive handling.
- The initial cost of the FRP reinforcing is considerably higher than traditional steel reinforcing



Long term durability of GFRP

✓ Materials are resistant to degradation, but over time...





- Degradation factors
  - Moisture
    - Diffusion through matrix
    - Flow through cracks or other flaws
    - Transportation medium for alkali/acid/salt
  - 🗸 Alkali
    - Attacks silica network in glass "etching and leaching"



GangaRao et al. Reinf. concr. des. with compos. CRC Press (2007)

- Degradation factors
  - ✓ Acids
    - Hydrogen replaces alkali and other positive mobile ions in glass "leaching"
  - Salts
    - Similar to acids
  - ✓ Temperature
    - Affects rate of moisture absorption and chemical reactions




GangaRao et al. Reinf. concr. des. with compos. CRC Press (2007)

Materials and processing


esign Tra

- Improvements made in material selection
  - Polyester to Vinyl Ester (less moisture absorption)
  - E glass to E-CR glass fibers (less leaching)






#### E glass fiber composite





Greenwood. Pultruded composites durability. Owens Corning (2001)


#### E-CR glass fiber composite





Greenwood. Pultruded composites durability. Owens Corning (2001)

#### • E vs E-CR glass fiber composites








Greenwood. Pultruded composites durability. Owens Corning (2001)


#### Materials and processing


- Quality of finished composite affects durability
  - Look for minimal defects and fully cured resin













Long term durability of GFRP

✓ Materials are resistant to degradation, but over time...

# **HOW MUCH TIME?**




Ada de la composición En composición de la c

- Long term durability of GFRP
  - Establish model(s) to accurately describe the degradation of GFRP based on the synergistic effects of physical and chemical aging on fibers, matrix and interface
  - Establish protocol for service life prediction based on the model(s)



#### Durability of CFRP

 Carbon fibers are highly stable, even in aggressive environments



Fibers from carbon/epoxy composite treated for 2 hours in 0.05 M KOH solution at 770°F, 4200 psi Individual fibers maintained 100% tensile strength



Knight et al. Environmental Technology 33, 639-644 (2012)

### **FDOT Resources**

Structures Design Office:

- A. Jordan Thomas, P.E. (FDOT Policy/Standards)
- Gevin McDaniel, P.E. (FDOT Policy/Standards)
- ✓ Sam Fallaha, P.E. (FDOT Research/Testing)
- ✓ Will Potter, P.E. (FDOT Research/Testing)
- Materials Office:
  - Chase Knight, PhD (Materials/Durability)



Composites and Advanced Materials Expo October 13-16, 2014 Orange County Convention Center Orlando, FL

#### THE COMPOSITES AND ADVANCED MATERIALS EXPO

#### COMBINED STRENGTH UNSURPASSED INNOVATION.

October 13-16, 2014: Conference / October 14-16, 2014: Exhibits Orlando, Fl / Orange County Convention Center

#### <u>www.thecamx.org</u>







Society for the Advancement of Material and Process Engineering



